


Style	Grade	Basis weight g/m <sup>2</sup>	Tensile strength N/50mm			
			Nomal		Flame retardant 	
			MD	CD	MD	CD
TY (MD/CD)	TY0503FE	8	25	10	15	10
	TY0505FE	10	25	16	15	15
	TY1010FE	20	55	40	50	40
	TY1515FE	30	100	65	75	65
	TY2020FE	40	160	90	105	90
	TY2525FE	50	180	120	-	-
	TY3030FE	60	230	150	-	-
T (MD only)	TY4020FE	60	300	90	220	90
	T 05	5	20	-	15	-
	T 10	10	50	-	50	-
	T 15	15	90	-	75	-
	T 20	20	140	-	105	-
	T 25	25	170	-	-	-
	T 30	30	200	-	-	-
	T 40	40	280	-	220	-

For the flame retardant types, please add "B" to the each grade code.

\*The information contained herein is furnished without charge or obligation and the recipient assumes all responsibility for its use.

Because conditions of use and handling may vary and are beyond our control, we make no representation about, and are not responsible or liable for, the accuracy or reliability of said information or the performance of any product.

Any specifications, properties or applications listed herein are provided as information only and in no way modify, amend, enlarge or create any warranty.

Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.

MILIFE® is a registered trademark of the ENEOS techno material Corporation (old company name JX ANCI Corporation).